

International MF/HF <u>Voice</u> Distress, Safety, & Hailing Frequencies			
Ship Tx	Ship Rx	Simplex / Duplex	USB / LSB
2182.0 kHz	2182.0 kHz	Simplex	USB
4125.0 kHz	4125.0 kHz	Simplex	USB
6215.0 kHz	6215.0 kHz	Simplex	USB
8291.0 kHz	8291.0 kHz	Simplex	USB
12290.0 kHz	12290.0 kHz	Simplex	USB
16420.0 kHz	16420.0 kHz	Simplex	USB

International MF/HF <u>DSC</u> Distress & Hailing Frequencies			
Ship Tx	Simplex / Duplex	USB / LSB	Voice
2187.5 kHz	Simplex	USB	2182.0 kHz
4207.5 kHz	Simplex	USB	4125.0 kHz
6312.0 kHz	Simplex	USB	6215.0 kHz
8414.5 kHz	Simplex	USB	8291.0 kHz
12577.0 kHz	Simplex	USB	12290.0 kHz
16804.5 kHz	Simplex	USB	16420.0 kHz
The simplex DSC frequencies are guarded and are used for digital alerting and calling for distress, urgency, and safety. Once the DSC call has been sent, the corresponding radiotelephone frequency is used for voice communications.			